

LED NITEHAWK PATROL LIGHT

**LED DELIVERS A CRISP 9° SPOT BEAM
WITH A BRILLIANT 1,000 LUMENS FROM
ANY 12-VOLT SOURCE •**

**CUTTING-EDGE LED BULB LASTS OVER
THREE HUNDRED TIMES LONGER THAN
TRADITIONAL HALOGEN BULBS**

**COMFORTABLE PISTOL GRIP STOCK
WITH SMOOTH ACTION ROCKER SWITCH**

**D-RING HANGER FOR CONVENIENT
STORAGE ON THE JOB**

**LIGHT-WEIGHT (UNDER 3 LBS.) AND
EXTREMELY RUGGED, MADE TO
OUTLAST ALL OTHERS IN ITS CLASS**

This weatherproof, indestructible LED spotlight is preferred by the industries where harsh environments and hazardous duty are an everyday occurrence. Single piece body and industrial quality coil cord add to the virtually indestructible design and construction; offering incredible versatility and unmatched performance.

Enjoy your choice of momentary or on/off style switch in a convenient pistol grip handle for ease of operation over extended periods. Only 9-inches by 5-inches and less than 3-Lbs., the LED Nitehawk Patrol Light can deliver a powerful burst of light that can penetrate through glass, smoke, and fog in a small, easy to carry package.

Thousands of the original Nitehawk Patrol Light have been sold and are used all over the nation by police, ambulance, fire departments, highway and sewer maintenance, construction, marine and oil/chemical plants, and more. You'll find that the new LED Nitehawk is brighter, more efficient, and longer lasting, so it can continue to deliver dependability in severe conditions again and again.



SPECIFICATIONS

Nitehawk Series: 2000L

Housing: One piece Unibody UV treated black EPDM

Switch: Momentary spring-loaded rocker switch.
Heavy-Duty ON/OFF switch also available.

Cord: 18/2 SVO coil cord
(2' retracted - 12' extended).
Double length also available.

Lamp: L901 - 1,000 Lumens, 18.5 Watt
12 +/- 1.2 Volts, 1.54 Amps, GaN-on-GaN
3000K Color Temp, 9° Beam Angle
35,000 hour lamp life

Plug: Heavy-duty Cigarette Plug.
4-Pole Trailer Plug also available.

Weight: Light = 2.8 Lbs. Shipping = 3.25 Lbs.

Dimensions: Diameter = 4.5" Length= 8.5"